SUPREME TUBE TESTER MODEL 89-D TUBE LIST

(Specify "S" Series Tube Chart When Re-ordering)

NON-OCTAL TUBES

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
1A4	2.0	7	76.5	F
1A6	2.0	7	75.0	F
1B4	2.0	7	76.5	F
1B5/25S/25	2.0	7	73.0	F
1C6	2.0	7	65.0	F
1F4	2.0	7	60.5	F
2A3/2A3H	2.5	7	34.0	F
2A5	2.5	7	53.0	5
2A6/2A6S	2.5	7	55.5	5
2A7/2A7S	2.5	7	53.0	6
2B6	2.5	7	59.0	5&6
2B7/2B7S	2.5	7	59.0	6
2Y4	2.5	7	40.0	4
2Z2/G84	2.5	7	74.0	F
5Z3	5.0	7	44.0	F
6A3	6.3	7	39.0	F
6A4/LA	6.3	7	56.0	F
6A6	6.3	7	34.5	4
6A7/6A7S	6.3	7	54.0	6
6B5	6.3	7	63.0	F&5
6B6	6.3	7	56.0	5&6
6B7/6B7S	6.3	7	60.5	6
6C6	6.3	7	53.5	5
6C7	6.3	7	52.5	6
6D6	6.3	7	53.5	5
6D7	6.3	7	52.0	6
6E6	6.3	7	42.0	4
6E7	6.3	7	53.5	6
6F7/6F7S	6.3	7	55.5	6
6G7S/89RS	6.3	7	33.0	3&5
6H7S	6.3	7	55.0	6
6Y5/6Y5S	6.3	7	31.0	4
6Y5V	6.3	7	36.0	4
6Z3/1V	6.3	7	38.0	3
6Z4/84	6.3	7	32.0	4
6Z5	12.6(a)	7	32.0	4
12A5	12.6(b)	7	47.5	5
12A7	12.6	7	29.5	4&6
12Z3/14Z3	12.6	7	30.0	3
12Z5	12.6(c)	7	26.0	3&5
14Z3/12Z3	12.6	7	30.0	3
25Y5	25.0	7	37.5	3&4
25Z5	25.0	7	20.0	3&4
00A	5.0	7	72.5	F
01A	5.0	7	74.5	F
01AA/01B	5.0	7	62.0	F
1	6.3	7	55.0	3
1V/6Z3	6.3	7	38.0	3
2S/4S	2.5	7	76.0	4
4S/[illegible]S	2.5	7	76.0	4

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
10	7.5	7	70.0	F
10X	7.5	7	68.5	F
12A	5.0	7	55.0	F
14	14.0	7	57.5	4
15	2.0	7	77.5	4
17	14.0	7	59.5	4
18	14.0	7	52.5	5
19	2.0	7	55.0	F
20	3.3	7	81.0	F
22-O	3.3	7	74.0	F
22-T	3.3	7	87.5	F
22 (Spec.)	14.0	7	59.0	F
24A/24S	2.5	7	57.0	4
25/25S/1B5	2.0	7	73.0	F
26	1.5	7	66.0	F
26 (Spec.)	14.0	7	55.0	F
27/27S	2.5	7	59.5	4
27HM/56	2.5	7	54.5	4
29	2.5	7	61.0	5
30	2.0	7	72.0	F
30 (Spec.)	14.0	7	61.0	F
30-X	2.0	7	72.5	F
31	2.0	7	70.0	F
32	2.0	7	74.0	F
32 (Spec.)	14.0	7	53.0	F
33	2.0	7	60.0	F
34	2.0	7	74.5	F
35/51	2.5	7	57.0	4
35S/51S	2.5	7	57.0	4
36/36A	6.3	7	52.0	4
37/37A	6.3	7	55.0	4
38/38A	6.3	7	59.5	4
39/44/39A	6.3	7	56.0	4
40	5.0	7	70.5	F
10 (Spec.)	14.0	7	50.5	F
41	6.3	7	52.5	5
42	6.3	7	51.5	5
43	25.0	7	41.5	5
44/39/39A	6.3	7	56.0	4
45	2.5	7	56.0	F
46	2.5	7	54.0	F
47/PZ	2.5	7	54.5	F
48	30.0	7	35.0	5
48 (Spec.)	14.0	7	57.0	F
49	2.0	7	66.5	F
50	7.5	7	67.0	F
51/35	2.5	7	57.0	4
51S/35S	2.5	7	57.0	4
52	6.3	7	54.0	F
53	2.5	7	33.5	4
55/55S	2.5	7	57.0	5
56/56S	2.5	7	54.5	4
56AS	6.3	7	54.0	4

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
57/57S	2.5	7	52.5	5
57AS	6.3	7	52.0	5
58/58S	2.5	7	52.5	5
58AS	6.3	7	53.0	5
59	2.5	7	52.5	6
59B	2.5	7	54.0	F
64	6.3	7	61.5	4
64A	6.3	7	52.5	4
65	6.3	7	55.0	4
65A	6.3	7	56.0	4
67	6.3	7	58.5	4
67A	6.3	7	54.0	4
68	6.3	7	53.5	4
68A	6.3	7	57.5	4
69	6.3	7	65.5	5
70	6.3	7	77.0	5
71A/482A	5.0	7	57.5	F
75/75S	6.3	7	50.5	5
76	6.3	7	54.5	4
77	6.3	7	53.0	5
78	6.3	7	55.5	5
79	6.3	7	36.0	4
80	5.0	7	55.5	F
80M/83	5.0	7	7.5	F
81/81M	7.5	7	77.5	F
82/AF	2.5	7	8.0	F
83/AG/986	5.0	7	7.5	F
83V	5.0	7	27.5	F
84/6Z4	6.3	7	32.0	4
85/85S	6.3	7	55.0	5
85AS	6.3	7	53.0	5
86	6.3	7	55.5	4
87S	6.3	7	52.0	5
88/83	5.0	7	7.5	F
88S	6.3	7	53.0	5
89	6.3	7	54.5	5
89RS/6G7S	6.3	7	33.0	3&5
95/2A5	2.5	7	53.0	5
96/1V	6.3	7	38.0	3
98/84	6.3	7	32.0	4
99-O	3.3	7	81.5	F
99-T	3.3	7	80.0	F
181	3.3	7	70.0	F
182B/482B	5.0	7	58.0	F
183/483	5.0	7	58.0	F
205-D	5.0(e)	7	70.0	F
213/80	5.0	7	55.0	F
216/216B/81	7.5	7	77.5	F
257	5.0	7	59.5	F
401	3.3	7	65.0	F
403	3.3	7	59.5	F
482A/71A	5.0	7	57.5	F
482B/182B	5.0	7	58.0	F

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
483/183	5.0	7	58.0	F
484	3.3	7	52.0	4
484A	2.5	7	54.5	4
485	3.3	7	56.0	4
486/686	3.3	7	75.5	F
585/586/50	7.5	7	67.0	F
686/486	3.3	7	75.5	F
950	2.0	7	64.5	F
951	[illegible].0	7	68.5	F
985/84/6Z4	6.3	7	32.0	4
986/83	5.0	7	7.5	F
AD/6Z3/1V	6.3	7	38.0	3
AF/82	2.5	7	8.0	F
AG/83	5.0	7	7.5	F
DE1/27/27S	2.5	7	59.5	4
GA	5.0	7	54.5	F
G84/2Z2	2.5	7	74.0	F
KR-1	6.3	7	38.0	3
KR-5	6.3	7	56.0	F
KR-20	3.3	7	53.0	5
LA/6A4	6.3	7	56.0	F
P861/84/6Z4	6.3	7	32.0	4
PA	6.3	7	55.0	4
PZ/47	2.5	7	54.5	F
PZH	2.5	7	56.5	6
R-20	2.5	7	63.0	F
R-30	2.5	7	67.5	4
R-32	2.5	7	68.0	F
R-100	5.0	7	70.0	F
R-200	5.0	7	66.0	F
RE1/80	5.0	7	55.5	F
RE2/81	7.5	7	77.5	F
RK-24	2.0	7	63.5	F
SO2/50	7.5	7	67.0	F
WUND-A	2.5	7	58.5	5
WUND-AA	6.3	7	59.0	5

Future Non-Octal Tubes

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----

OCTAL TUBES

NOTE:—Octal types differing in designation from the following by an additional final letter "G", "M", "MG" are interchangeable in general, regardless of the letter, as it simply denotes the type of shell employed by individual manufacturers, and take the same tester settings.

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
2A6	2.5(d)	7	51.5	8
5Y3	5.0	8	54.0	F
5Z4	5.0	8	34.0	F
6A7	6.3(d)	7	54.0	8
6A8	6.3(d)	7	53.5	8
6B6	6.3(d)	7	56.0	4&8
6B7	6.3(d)	7	60.5	8
6C5	6.3(d)	7	53.5	8
6D5	6.3(d)	7	54.5	8
6F5	6.3(d)	7	47.0	8
6F6	6.3(d)	7	54.0	8
6F7	6.3(d)	7	55.5	8
6H6	6.3	7	92.5	4&8
6H7	6.3(d)	7	55.0	8
6J7	6.3(d)	7	53.0	8
6K6	6.3(d)	7	60.0	8
6K7	6.3(d)	7	54.0	8
6L6	6.3(d)	7	39.5	8
6L7	6.3(d)	7	44.5	8
6N6	6.3(d)	7	62.0	8
6P7	6.3(d)	3	56.0	8
6Q7	6.3(d)	7	52.0	8
6R7	6.3(d)	7	53.0	8
6X5	6.3(d)	7	33.0	8
6Z6	6.3(d)	7	31.0	4&8
25A6	25.0(d)	7	44.0	8
25Z5	25.0(d)	7	19.0	4&8
25Z6	25.0(d)	7	24.5	4&8
24	2.5(d)	7	58.0	8
27	2.5(d)	7	58.5	8
35/51	2.5(d)	7	57.0	8
41	6.3(d)	7	52.5	8
43	25.0(d)	7	39.0	8
51/35	2.5(d)	7	57.0	8
55	2.5(d)	7	57.0	8
56	2.5(d)	7	54.5	8
57	2.5(d)	7	53.5	8
58	2.5(d)	7	57.0	8
75	6.3(d)	7	52.0	8
77	6.3(d)	7	54.5	8
78	6.3(d)	7	57.5	8
80	5.0	8	54.5	F
85	6.3(d)	7	56.0	8
86	6.3(d)	7	55.5	8
88	6.3(d)	7	53.0	8

Future Octal Tubes

Type	Fil.V. Slctr.	Fil. Ret. Slctr.	Qlty. Slctr.	Buttons
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----
------	------	----	------	----

(a) Throw the "6Z5" tumbler switch from the "NORMAL" to the "6Z5" position during the test.
(b) Throw the "12A5" tumbler switch from the "NORMAL" to the "12A5" position during the test.
(c) Throw the "12Z5" tumbler switch from the "NORMAL" to the "12Z5" position during the test.
(d) Throw the "12A5" and the "12Z5" tumbler switches from the "NORMAL" to the "12A5" and "12Z5" positions during the test.
(e) Use No. 7530 Adapter.

SUPREME INSTRUMENTS CORPORATION

GREENWOOD, MISSISSIPPI, U. S. A.

STOCK NO. [illegible]144-KS

PRINTED IN U. S. A.